

DWMP1



Video	
Input	
Input Signal	1 HDMI, 1 VGA, 1 AUDIO, 1 IR, 1 RS232
Connector	1 19-pin Type A HDMI female; 1 15-pin VGA; 1 3.5mm stereo jack; 1 3.5mm IR socket; 1 3-pin pluggable terminal block
Output	
Output Signal	1 HDBaseT, 1 IR
Connector	1 RJ45; 1 3.5mm IR socket
Transmission Mode	HDBaseT
Audio	
Frequency Response	20Hz~20KHz
Impedance	>10Ω
SNR	>85db@20Hz~20KHz
General	
Resolution	VGA: 800 x600, 1024 x 768, 1280 x 800, 1280 x 1024, 1440 x 900, 1600 x 1200, 1920 x 1080, 1920 x 1200; HDMI: 4Kx2K, 1080p 3D, 1080P(HD)/1080i/720P/576P/576i/480P/480i
Transmission Distance	1080P≤60M (PoC) 4Kx2K≤40M (PoC)
Bandwidth	10.2Gbps
HDMI Standard	Support HDMI1.4 and HDCP
Power Supply	DC 12V 2A; 9.6W
Temperature	-10 ~ +40℃
Humidity	10% ~ 90%
Dimension	US two gang (120 W x 120 H x 75 D)

