

# MCA 804V



## Multi-Channel 4 Channel Power Amplifier With Bridged System With 100V Transformer

Spec	Model	MCA 804V
<b>Input</b>		
Input Sensitivity		< 1.0V at 4 Ohms
Input Connector		RCA
Input Impedance		30K ohms (unbalanced)
<b>Output</b>		
Output Power At (<1%T.H.D)		60 W/ch at 8 Ohms 80 W/ch at 4 Ohms 160 W (Bridged) at 8 Ohms
Output		50.70.100V (at 80W)
Output Connector		EUR black
Frequency Response		+/- 3 dB 20 Hz To 40 KHZ
T.H.D Distortion		<0.02% at (20 to 20 KHz)
Hum & Noise		< -90 dB (referred to PRO)
<b>General</b>		
Finish		Black (power coat)
Front Mounted		Power ON/OFF Volume Control
Rear Mounted		Stereo/Bridged Switch Signal Link Switch
Crosstalk		< 60 dB At 1KHz
Voltage Gain		30 dB
Damping Factor		>100 (for loads 4 Ohms at 20 to 20KHz)
Power Requirements		480VA 110/120 VAC 50/60 Hz 220/240 VAC 50/60 Hz
Dimension (W*H*D)		44 x 481 x 350 mm
Net Weight		6.0 Kg