

# ENGINEERING FOR QUALITY

**EUROSOUND**

The product is a HDMI switcher accommodates 4 HDMI inputs. Select any of the inputs by front panel button or IR Remote, the corresponding indicator on the front panel will illuminate to show real-time I/O connection status. Compliance with HDMI 1.4& HDCP1.4, it can transmit non-depressed 4K (at max) signal. The HDMI switcher boasts comprehensive audio capacities including PCM, Dolby Digital, DTS, and DTS-HD. Besides, it provides an ARC audio output socket to transfer ARC audio to ARC speakers like Yamaha. Moreover, it supports convenient online firmware update through USB port.

AV PROCESSOR

## UH0401A HDMI Switcher



**EUROSOUND**

For any enquiry please contact us.

Email: [sales@eurossound.co](mailto:sales@eurossound.co)

[WWW.EUROSOUND.CO](http://WWW.EUROSOUND.CO)

ENGINEERING FOR QUALITY

# UH0401A

## HDMI Switcher



### MAIN FEATURES

- 4 HDMI inputs
- Support Hot-plug
- HDMI 1.4 compliant , capable of 4K signal
- Support auto-detecting for input HDCP
- Support EDID management,
- Intuitive indicators for power, switch mode, I/O connection status and audio output signal
- Convenient online firmware update

### SPECIFICATION

#### 4K HDMI Switcher 4x1

HDMI Standard	HDMI 1.4, support HDMI Deep Color, full 3D & 4Kx2K@30Hz
HDCP	HDCP 1.4 compatible
Video Signal	(1) Support VESA and SMPTE Video 480p/1024x768/720p//1280x800/1080p/3840x2160@30Hz
ARC	HDMI support ARC function
Bandwidth	10.2Gbps
IR Control	IR IN, DC 5V,connect to the IR receiver and receive the IR signal of IR remote
Input	HDMI x4; 3.5mm(IR IN) x1
Output	HDMI x1; 3.5mm(audio) x1
Other Connector	RS232(3.5mm) x1; DIP(EDID for 4P) x1; Power Connector x1
HDMI Connector	Type A
3.5mm Connector	IR IN x1 / audio x 1 /RS232 x 1
Chassis Dimension	W194 x H11.4 x D80(mm), ultra-thin
Raw Materials	Aluminum chassis
Weight	About 160g
Power Supply	DC 5V 1A
Power Consumption	4.2W (Max)
Work Temperature	-10 ~ +40°C
Relative Humidity	10% - 90%