

# ENGINEERING FOR QUALITY

**EUROSOUND**

The HDMI 2.0 1x4 Splitter, which can distribute one HDMI input to four outputs. The splitter supports HDMI video resolution up to 4K@60Hz 4:4:4, 1080p 3D, and multichannel audio formats. Besides passing EDID information from the display, there are multiple built-in EDID settings can be selected by the 4-pin DIP switch on the front panel. Moreover, the splitter supports convenient firmware upgrade through Micro-USB port.

AV PROCESSOR

## HHDA4 HDMI 2.0 Splitter



**EUROSOUND**

For any enquiry please contact us.

Email: [sales@eurossound.co](mailto:sales@eurossound.co)

[WWW.EUROSOUND.CO](http://WWW.EUROSOUND.CO)

ENGINEERING FOR QUALITY

# HDDA4

## HDMI 2.0 Splitter



### MAIN FEATURES

- Supports HDMI 2.0 up to 4K@60Hz 4:4:4.
- Input HDCP 2.3; outputs HDCP Active/Passive
- Supports down-scaling to 1080p
- 18Gbps high bandwidth.
- Advanced EDID management
- Built-in equalizer for signal enhancement
- Supports CEC pass-through.
- Firmware upgrade by Micro-USB port.

### SPECIFICATION

Video Input	
Input	(1) HDMI
Input connector	(1) Type-A female HDMI
HDMI Input Resolution	Up to 4Kx2K@60Hz 4:4:4 8bit
HDMI Standard	2.0
HDCP Version	2.3, 1.4 compliant
CEC	Supported
Video Output	
Output	(4) HDMI
Output connector	(4) Type-A female HDMI
HDMI Output Resolution	Up to 4Kx2K@60Hz 4:4:4 8bit
HDMI Standard	2.0
HDCP Version	2.3, 1.4 compliant
CEC	Supported
Control	
Control Part	(1) EDID 4-pin DIP switch, (1) Micro-USB port
General	
Bandwidth	18Gbps
HDMI 2.0 Cable Length	4K@60Hz 4:4:4 ≤ 5m, 4K@60Hz 4:2:0 ≤ 15m, 1080p ≤ 20m
Operation Temperature	-10°C ~ +55°C
Storage Temperature	-25°C ~ +70°C
Relative Humidity	10% - 90%
Power consumption	2.5W (Max)
Power supply	Input:100V~240V AC; Output: 5V DC 1A
Dimension (WxHxD)	142.0mm x 17.6mm x 70.4mm
Net weight	260g